



Nom. size	Outside dia.	Sling rod dia.	D dia.	Clip dim. B x T	P	Q	Clip & load bolts Bolt	Hole dia.	G min.	Safe working load
15	21.3	10	23	35 x 5	65	70	M10	12	15	280 KGF
20	26.9	10	28	35 x 5	70	70	M10	12	15	280 KGF
25	33.7	10	36	35 x 5	75	70	M10	12	15	280 KGF
32	42.4	12	44	35 x 5	90	70	M12	15	18	280 KGF
40	48.3	12	50	35 x 5	95	85	M12	15	18	280 KGF
50	60.3	12	62	35 x 5	105	80	M12	15	18	280 KGF
65	76.1	16	80	35 x 8	155	90	M16	19	24	450 KGF
80	88.9	16	92	35 x 8	165	95	M16	19	24	450 KGF
100	114.3	16	118	35 x 8	190	95	M16	19	24	450 KGF
125	139.7	16	144	35 x 8	215	95	M16	19	24	450 KGF
150	168.3	16	172	35 x 8	245	95	M16	19	24	450 KGF
175	193.7	20	198	45 x 10	288	85	M20	24	30	900 KGF
200	219.1	20	224	45 x 10	315	95	M20	24	30	900 KGF
225	244.5	20	248	60 x 15	365	85	M20	24	30	1350 KGF
250	273.0	20	278	60 x 15	390	90	M20	24	30	1350 KGF
300	323.9	24	330	65 x 20	475	115	M24	28	36	1800 KGF
350	355.6	30	362	65 x 20	525	115	M30	35	45	2250 KGF
400	406.4	30	412	90 x 25	600	115	M30	35	45	2700 KGF
450	457.0	36	464	90 x 25	660	115	M36	42	54	3600 KGF
500	508.0	36	516	100 x 30	740	115	M36	42	54	4500 KGF
550	559.0	36	566	100 x 30	790	115	M36	42	54	4500 KGF
600	610.0	42	618	100 x 35	880	115	M42	48	63	5900 KGF

All dimensions in mm. Up to 350NB size in stock, larger sizes made to order.

**Finishes available:**

- Self Colour
- Galvanised

**BS 3974  
BS EN 10025**

**Temperature range  
-20°C to 100°C**